

UNIT SIZE	SINGLE HOUSE (compliant with UK Building Regulations)		MULTIPLE HOUSES	
	BA	BA-X	BB	BC
Population equivalent	6	9	12	18
Max. Daily BOD kg	0.36		0.72	1.08
Max. Daily Flow m <sup>3</sup>	1.2		2.4	3.6
Overall diameter mm	1995	1995	1995	2450
Inlet Invert Depth mm	750 *	750 *	750*	600 ^
Depth Below Inlet Invert mm	1400	1400	1400	1820
Outlet Invert Depth mm	1315	1315	1315	1735
Overall Height mm	2160/2460/2960	2160/2460/2960	2160/2460/2960	2825/3325
Height to Rim of Cover mm	1945/2245/2745	1945/2245/2745	1945/2245/2745	2485/2985
Empty Weight kg	310/325/380	310/325/380	335/350/405	650/750
Standard Power Supply	1 Phase	1 Phase	1 Phase	1 Phase
Full Load Current - Single Phase -amps	0.51	0.51	0.51	1.1
Optional Power Supply	3 Phase	3 Phase	3 Phase	3 Phase
Motor Rating - Three Phase	N/A	N/A	N/A	90
Full Load Current - Three Phase	N/A	N/A	N/A	0.38
Sludge Return Pump Rating	250W	250W	250W	250W
Electrical Power Consumption KWH/Year	682.55	682.55	682.55	923.45

\* Optional invert depths of 450mm and 1250mm are available.

^ Optional invert depth of 1100mm is available.

\*\* Optional integral pump available in BA, BA-X and BB models.

All Spec Data Displayed Within Table Above - Correct as at 11/09/17